

EPT44 H Specifications

EPT44 H Specifications		
Capacity	4400 lbs.	
Load Centre Distance	600 mm (23.6 in)	
Lift	4.5 in	
Fork Options	21.5in. x 45in. 27in. x 48in.	
Overall Length	61 in./63.8 in.	
Overall Width	27 in.	
Service Weight (Including battery)	330 lbs.	
Tires	Polyurethane	
Number of Wheels	1 driving +4(2) loading	
Turning Radius	53.2 in. / 56 in.	
Travel Speed	Laden: 2.5mph Unladen: 3.1mph	
Lift Speed	Laden: 0.03 in. (1.18) Unladen: 0.035 in. (1.38)	
Lowering Speed	Laden: 0.035 in. (1.38); Unladen: 0.025 in. (0.98)	
Max Gradeability	Laden: 6-deg Unladen: 20-deg	
Drive Modes	Turtle / Rabbit	
Drive Motor Voltage	48 V	
OLED Display	Battery Status, Machine Status	
Certifications	CE Certified	
Lithium-Ion Battery and Charger Specification *		
Battery	Voltage	48 V
	Capacity/Type	15Ah Lithium
	Run Time	3 Hr.
	Replace Time	6 seconds.
Charger	Charge Time	1.6 Hr (10A); 2.5 Hr (15A)
	Charger Type	External, 6A 48V
* CE certifications: electric pallet jack, battery and charger		

